

# COM 04

Anti-glare design  
SDCM<3 CRI>90  
Suitable for general lighting

**C04 . 28W 015 B IP20 927**

Model Power Beam angle Body color IP grade CCT

**Model**  
COM


**IP grade**  
IP20

**Power**  
28W [W]

**CCT**  
927 2700K  
930 3000K  
940 4000K  
950 5000K

**Beam angle**  
015 [°]  
024 [°]  
035 [°]  
050 [°]

**Body color**  
B Black  
W White



## Features

LED type	CREE
Color and CCT	2700K/3000K/4000K/5000K
Other colors	Upon request
Beam angle	15°/24°/35°/50°

## Performance

Max. delivered output	2600lm
Efficacy	104lm/W

## Electrical and control

Supply type	Main voltage (Integral LED driver)
Input voltage	AC240V
Max. power consumption	28W
Dimming	Upon request

## Physical

Cut out	125mm
Housing material	Aluminium
Optics material	PMMA
Weight	-
Operating temperature	-25/+55°C

## Accessories

Matt black reflector	ACC00122
Titanium reflector	ACC00123
Bright silver reflector	ACC00124
Matt silver reflector	ACC00125
Matt white reflector	ACC00126
Honeycomb D70	ACC00127
Smooth filter D70	ACC00128

