

PRE 02

High-end professional down light
Higher lumen output
SDCM<3 CRI>90
Multiple reflector finishing options



P02 . 12W **015** **B** **IP20** **927**

Model Power Beam angle Body color IP grade CCT

| | | | |
|-------------------|-----------------|--|--|
| Model | IP grade | | |
| PRE | IP20 | | |
| Power | CCT | | |
| 12W [W] | 927 2700K | | |
| | 930 3000K | | |
| Beam angle | 940 4000K | | |
| 015 [°] | 950 5000K | | |
| 024 [°] | | | |
| 035 [°] | | | |
| Body color | | | |
| B <i>Black</i> | | | |
| W <i>White</i> | | | |

Features

| | |
|---------------|-------------------------|
| LED type | CREE |
| Color and CCT | 2700K/3000K/4000K/5000K |
| Other colors | Upon request |
| Beam angle | 15°/24°/35° |

Performance

| | |
|-----------------------|---------|
| Max. delivered output | 1320lm |
| Efficacy | 110lm/W |

Electrical and control

| | |
|------------------------|------------------------------------|
| Supply type | Main voltage (Integral LED driver) |
| Input voltage | AC240V |
| Max. power consumption | 12W |
| Dimming | Upon request |

Physical

| | |
|-----------------------|-----------|
| Cut out | 75mm |
| Housing material | Aluminium |
| Optics material | PMMA |
| Weight | - |
| Operating temperature | -25/+55°C |

Accessories

| | |
|-------------------------|----------|
| Matt black reflector | ACC00259 |
| Titanium reflector | ACC00260 |
| Bright silver reflector | ACC00261 |
| Matt silver reflector | ACC00262 |
| Matt white reflector | ACC00263 |
| Honeycomb D40 | ACC00264 |
| Smooth filter D40 | ACC00265 |
| 15x70° Oval filter D40 | ACC00266 |

