


PRE 04

High-end professional down light
Higher lumen output
SDCM<3 CRI>90
Multiple reflector finishing options



P04 . 28W 015 B IP20 927

Model Power Beam angle Body color IP grade CCT

Model	IP grade
PRE	IP20
Power	CCT
28W [W]	927 2700K
	930 3000K
Beam angle	940 4000K
015 [°]	950 5000K
024 [°]	
035 [°]	
Body color	
B Black	
W White	

Features

LED type	CREE
Color and CCT	2700K/3000K/4000K/5000K
Other colors	Upon request
Beam angle	15°/24°/35°

Performance

Max. delivered output	2900lm
Efficacy	104lm/W

Electrical and control

Supply type	Main voltage (Integral LED driver)
Input voltage	AC240V
Max. power consumption	28W
Dimming	Upon request

Physical

Cut out	125mm
Housing material	Aluminium
Optics material	PMMA
Weight	-
Operating temperature	-25/+55°C

Accessories

Matt black reflector	ACC00275
Titanium reflector	ACC00276
Bright silver reflector	ACC00277
Matt silver reflector	ACC00278
Matt white reflector	ACC00279
Honeycomb D70	ACC00280
Smooth filter D70	ACC00281
15x70° Oval filter D70	ACC00282

