


PRE 05

High-end professional down light
Higher lumen output
SDCM<3 CRI>90
Multiple reflector finishing options



P05 . 36W **015** **B** **IP20** **927**

Model Power Beam angle Body color IP grade CCT

Model	IP grade
PRE	IP20
Power	CCT
36W [W]	927 2700K
	930 3000K
Beam angle	940 4000K
015 [°]	950 5000K
024 [°]	
035 [°]	
Body color	
B Black	
W White	

Features

LED type	CREE
Color and CCT	2700K/3000K/4000K/5000K
Other colors	Upon request
Beam angle	15°/24°/35°

Performance

Max. delivered output	3700lm
Efficacy	103lm/W

Electrical and control

Supply type	Main voltage (Integral LED driver)
Input voltage	AC240V
Max. power consumption	36W
Dimming	Upon request

Physical

Cut out	150mm
Housing material	Aluminium
Optics material	PMMA
Weight	-
Operating temperature	-25/+55°C

Accessories

Matt black reflector	ACC00283
Titanium reflector	ACC00284
Bright silver reflector	ACC00285
Matt silver reflector	ACC00286
Matt white reflector	ACC00287
Honeycomb D85	ACC00288
Smooth filter D85	ACC00289
15x70° Oval filter D85	ACC00290

