


PRE 06

High-end professional down light
Higher lumen output
SDCM<3 CRI>90
Multiple reflector finishing options

P06 . 06W 015 B IP20 927

Model Power Beam angle Body color IP grade CCT

Model	IP grade
PRE	IP20
Power	CCT
06W [W]	927 2700K
09W [W]	930 3000K
	940 4000K
Beam angle	950 5000K
015 [°]	
024 [°]	
035 [°]	
Body color	
B Black	
W White	



Features

LED type	CREE
Color and CCT	2700K/3000K/4000K/5000K
Other colors	Upon request
Beam angle	15°/24°/35°

Performance

Max. delivered output	700lm (6W) / 1000lm (9W)
Efficacy	117lm/W (6W) / 111lm/W (9W)

Electrical and control

Supply type	Main voltage (Integral LED driver)
Input voltage	AC240V
Max. power consumption	6W/9W
Dimming	Upon request

Physical

Cut out	76mm
Housing material	Aluminium
Optics material	PMMA
Weight	-
Operating temperature	-25/+55°C

Accessories

Matt black reflector	ACC00291
Titanium reflector	ACC00292
Bright silver reflector	ACC00293
Matt silver reflector	ACC00294
Matt white reflector	ACC00295
Honeycomb D40	ACC00296
Smooth filter D40	ACC00297
15x70° Oval filter D40	ACC00298

