

PRE 13

High-end professional down light
Higher lumen output
SDCM<3 CRI>90
Multiple reflector finishing options



P13 . 24W 015 B IP20 927

Model Power Beam angle Body color IP grade CCT

Model	IP grade
PRE	IP20
Power	CCT
24W [W]	927 2700K
	930 3000K
Beam angle	940 4000K
015 [°]	950 5000K
024 [°]	
035 [°]	
Body color	
B Black	
W White	

Features

LED type	CREE
Color and CCT	2700K/3000K/4000K/5000K
Other colors	Upon request
Beam angle	15°/24°/35°

Performance

Max. delivered output	2500lm
Efficacy	104lm/W

Electrical and control

Supply type	Main voltage (Integral LED driver)
Input voltage	AC240V
Max. power consumption	24W
Dimming	Upon request

Physical

Cut out	100x100mm
Housing material	Aluminium
Optics material	PMMA
Weight	-
Operating temperature	-25/+55°C

Accessories

Matt black reflector	ACC00347
Titanium reflector	ACC00348
Bright silver reflector	ACC00349
Matt silver reflector	ACC00350
Matt white reflector	ACC00351
Honeycomb D55	ACC00352
Smooth filter D55	ACC00353
15x70° Oval filter D55	ACC00354

