


PRM 10W

High performances
Minimal design
Integrated driver
SDCM<3 CRI>90
Dimming options available



PRM. 10W **NN** . **012** **B** **927**

Model Power Dimming Beam angle Body color CCT

Model

PRM

Body color

B *Black*
W *White*

Power

10W [W]

CCT

927 2700K
930 3000K
940 4000K

Dimming

NN *none*
DA *Dali*
1V *1-10V*
PM *Potentiometer*
TR *TRIAC*

Beam angle

012 [°]
024 [°]
036 [°]
060 [°]

Features

LED type	CREE
Standard CCT	2700K/3000K/4000K
Other CCT upon request	5000K/6000K
Beam angle	12°/24°/36°/60°

Performance

Max. delivered output	865 – 1017lm
Efficacy	87 – 102lm/W

Electrical and control

Supply type	Main voltage
Input voltage	AC240V
Max. power consumption	10W
Dimming option	See table of codes

Physical

Housing material	Aluminium
Optics material	PMMA
Weight	0.62kg
Operating temperature	-25/+55°C

Accessories

Honeycomb	ACC00503
Cross louver	ACC00504
Barn door	ACC00505
Filter - circular small	ACC00512
Filter - circular big	ACC00513
Filter - square	ACC00514
Filter - rectangular	ACC00515
Filter - wall washing	ACC00516

