


PRZ 20W

Adjustable beam angle
Minimal design
Integrated driver
SDCM<3 CRI>90
Dimming options available



PRZ .20W **NN** . **2560** **B** **927**

Model Power Dimming Beam angle Body color CCT

Model

PRZ

Beam angle

2560 25÷60 [°]

Power

20W [W]

Body color

B *Black*
W *White*

Dimming

NN *none*
DA *Dali*
1V *1-10V*
PM *Potentiometer*
TR *TRIAC*

CCT

927 2700K
930 3000K
940 4000K

Features

LED type	CREE
Standard CCT	2700K/3000K/4000K
Other CCT upon request	5000K/6000K
Beam angle	25÷60°

Performance

Max. delivered output	1706 – 2004lm
Efficacy	85 – 100lm/W

Electrical and control

Supply type	Main voltage
Input voltage	AC240V
Max. power consumption	20W
Dimming option	See table of codes

Physical

Housing material	Aluminium
Optics material	PMMA
Weight	1kg
Operating temperature	-25/+55°C

Accessories

Honeycomb	ACC00528
Filter - circular small	ACC00529
Filter - circular big	ACC00530
Filter - square	ACC00531
Filter - rectangular	ACC00532
Filter - wall washing	ACC00533

