


# 1220RGB

IP68 protection with full Polyurethane encapsulation. With PC Profile, perfect for underwater applications like swimming pools. Ideal for resorts, seaside parks and luxurious yachts decoration. It is a professional solution for architectural and facade lighting.



## Specifications

### Features

LED type	Mid-power SMD
LED nr.	84LEDs/m
Standard CCT	RGB
Other CCT upon request	N.A.
Beam angle	Diffuse

### Performance





Lumen output (at 85°C)	240lm/m (full color)
Color rendering index	N.A.
Efficacy	18lm/W (R) / 45lm/W (G) / 11lm/W (B)

### Electrical and control

Supply type	Constant voltage
Input voltage	DC24V
Input current	0.42A/m (full load)
Max. power consumption	10W/m (full load)
Dimming	External


### Physical

Minimum cut	71.5mm
Max length	5000mm
Bending radius	150mm
Weight	0.35kg/m
Operating temperature	-25/+55°C
ESD Protection	+/- 2000V




Pictures and sketches have only an information purpose and the products can change form, color and performances without any prior notice.

## Accessories




### Aluminium profile L=200 cm

Code	ACC00706
Material and color	Aluminium (silver)



### Stainless steel flexible profile L=100 cm

Code	ACC00707
Material and color	Polycarbonate (transparent)



### Mounting clips

Code	ACC00708
Material and color	Stainless steel (silver)



### IP68 4 poles connector kit (male/female)

Code	ACC00714
Diameter	23 mm



### Black round PU cable - 4 cores

Code	ACC00718
Wires section	4X0,5 mm <sup>2</sup>

## How to order

**1220RGB 10W XXXX F . RGB**

Model

Power

Lenght

Cable entry

CCT

**Model**  
1220RGB

**Lenght**  
XXXX [mm]

**CCT**  
RGB    RGB

**Power**  
10W [W/m]

**Cable entry**  
F    *Front*  
L    *Left side*  
R    *Right side*  
B    *Bottom*