


1220RGBW

IP68 protection with full Polyurethane encapsulation. With PC Profile, perfect for underwater applications like swimming pools. Ideal for resorts, seaside parks and luxurious yachts decoration. It is a professional solution for architectural and facade lighting.



Specifications

Features

LED type	Mid-power SMD
LED nr.	84LEDs/m
Standard CCT	RGB + 2700K/3000K/4000K/6500K
Other CCT upon request	N.A.
Beam angle	Diffuse

Performance

Lumen output (at 85°C)	430lm/m (full color)
Color rendering index	>90 (white only)
Efficacy	14lm/W (R) / 41lm/W (G) / 10lm/W (B) 52m/W (White)




Electrical and control

	Constant voltage
	DC24V
Input voltage	0.625A/m (full load) 15W/m (full load)
Max. power consumption	External

Physical


	71.5mm
	5000mm
Max length	150mm
	0.35kg/m
Weight	-25/+55°C +/- 2000V

ESD Protection




Pictures and sketches have only an information purpose and the products can change form, color and performances without any prior notice.

Accessories




Aluminium profile L=200 cm

Code	ACC00706
Material and color	Aluminium (silver)



Stainless steel flexible profile L=100 cm

Code	ACC00707
Material and color	Polycarbonate (transparent)



Mounting clips

Code	ACC00708
Material and color	Stainless steel (silver)



IP68 5 poles connector kit (male/female)

Code	ACC00715
Diameter	14 mm



Black round PU cable - 5 cores

Code	ACC00719
Wires section	1.0 mm ²

How to order

1220RGBW 15W XXXX F . CC2

Model	Power	Lenght	Cable entry	CCT
-------	-------	--------	-------------	-----

Model	Lenght	CCT	
1220RGBW	XXXX [mm]	CC2	RGB + 2700K
		CC3	RGB + 3000K
Power	Cable entry	CC4	RGB + 4000K
15W [W/m]	F Front	CC6	RGB + 6500K
	L Left side		
	R Right side		
	B Bottom		