


# COB 528

Uniform light emission, zero dark spot  
 COB encapsulation without wire bonding  
 Flip chip technology  
 3M double-sided tape  
 150 mm feeding wires  
 Max lenght from single connection: 5m



**COB 15W 528 IP20 . 927**

Model Power LED nr. IP grade CCT

Model	CCT	
COB	927	2700K
	930	3000K
	940	4000K
Power 15W [W/m]	950	5000K
	960	6000K
	960	6000K
LED Nr. 528 [led/m]		
IP grade IP20		

## Features

LED type	COB
LED nr.	528LEDs/m
Standard CCT	2700K/3000K/4000K/5000K/6000K
Other CCT upon request	N.A.
Beam angle	180°

## Performance


Lumen output (at 85°C)	1420 – 1600lm/m (435 – 490lm/ft)
Color rendering index	>90
Efficacy	94 – 106lm/W

## Electrical and control

Supply type	Constant voltage
Input voltage	DC24V
Input current	0.625A/m (0.19A/ft)
Max. power consumption	15W/m (4.62W/ft)
Dimming	External

## Physical

Minimum cut	50mm (1.97")
Reel length	5m (16.40')
Weight	0.05kg/m
Operating temperature	-25/+55°C
ESD Protection	+/- 2000V



Note: not all combinations of technical features are possible, please check with our technical office at the email address: [sales@elinca.it](mailto:sales@elinca.it)