APEX 3



Features

Introducing our APEX 3, featuring a lumen output of 2405lm to 3336lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product features two adjustable beam angles, ranging from 24° to 50°, making it ideal for trendy outdoor restaurant. With an IP65 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Applications

APEX surface-mounted outdoor downlights combine durability, style, and functionality, delivering focused illumination with sleek designs. Easy to install, they adapt seamlessly to various outdoor environments, making them ideal for entrances, covered walkways, terraces, patios, and building facades. Their robust constructions ensure reliable performance in all weather conditions, enhancing safety and ambiance while maintaining modern, clean aesthetics that complement any architectural style or outdoor setting.























www.elinca.it Downlights

APEX 3 - 20W	Optics	Output	ССТ	Part number
	24°	2415lm 2608lm 2897lm	2700K 3000K 4000K	1005.20W024□927 1005.20W024□930 1005.20W024□940
	50°	2405lm 2597lm 2886lm	2700K 3000K 4000K	1005.20W050□927 1005.20W050□930 1005.20W050□940
☐ refers to finishing: B: Black, W: White. Standard configuration: W, white body, mirror silver reflector. Other CCT upon request.				

APEX 3 - 25W	Optics	Output	ССТ	Part number
	24°	2780lm 3002lm 3336lm	2700K 3000K 4000K	I006.25W024□927 I006.25W024□930 I006.25W024□940
	50°	2768lm 2990lm 3322lm	2700K 3000K 4000K	I006.25W050□927 I006.25W050□930 I006.25W050□940
☐ refers to finishing: B: Black, W: White. Standard configuration: W, white body, mirror silver reflector. Other CCT upon request.				

Accessories	Description	Part number
	Matt black reflector	ACC01057
	Matt white reflector	ACC01058
	Mirror silver reflector	ACC01059