

ECO-R 2



Light output: up to 1275lm **Cut out:** ø90mm **Standard finishing:** ● ○

Features

Showcasing our ECO-R 2, featuring a lumen output of 1063lm to 1275lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This adaptable product offers a 90° beam angle, making it ideal for spaces and offices. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

ECO-R downlights are perfect for general area lighting, offering a soft, diffuse light throughout the space. Their slim designs make them ideal for low-ceiling areas with limited depth. The textured opal screen ensures a smooth, high-quality light output, enhancing the atmosphere with a clean and even illumination. Versatile and efficient, these downlights are perfect for both working and commercial settings. Whether in hallways, offices, or other spaces, ECO-R downlights delivers reliable, subtle lighting that enhances any environment with style and efficiency.



ECO-R 2 - 9W	Optics	Output	CCT	Part number
	90°	1063lm	2700K	A059.09W090□927
		1148lm	3000K	A059.09W090□930
		1275lm	4000K	A059.09W090□940
<div>□ refers to finishing: B: Black, W: White. Other CCT upon request.</div>				