


ECO-SQ 1



Features

Highlighting our ECO-SQ 1, featuring a lumen output of 1095lm to 1315lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This adaptable product offers a 90° beam angle, making it ideal for spaces and offices. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

ECO-SQ downlights are perfect for general area lighting, offering a soft, diffuse light throughout the space. Their slim designs make them ideal for low-ceiling areas with limited depth. The textured opal screen ensures a smooth, high-quality light output, enhancing the atmosphere with a clean and even illumination. Versatile and efficient, these downlights are perfect for both working and commercial settings. Whether in hallways, offices, or other spaces, ECO-SQ downlights deliver reliable, subtle lighting that enhances any environment with style and efficiency.



ECO-SQ 1 - 9W	Optics	Output	CCT	Part number
	90°	1095lm	2700K	A063.09W090□927
		1183lm	3000K	A063.09W090□930
		1315lm	4000K	A063.09W090□940
<div>□ refers to finishing: B: Black, W: White. Other CCT upon request.</div>				