FLAT 4



Features

Highlighting our FLAT 4, featuring a lumen output of 3428lm to 5878lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This adaptable product offers a 90° beam angle, making it ideal for hotel exteriors. With an IP65 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

FLAT are recessed downlights specifically designed for outdoor applications, offering soft, diffuse light with slim, sleek designs. Their compact sizes make them ideal for low-ceiling areas with limited depth, providing efficient lighting solutions in spaces where space is at a premium. Perfect for outdoor working areas, these downlights offer clean, even illumination, creating inviting atmospheres while maintaining high energy efficiency. Whether for patios, walkways, or other outdoor environments, FLAT downlights deliver reliable, attractive lighting.



























www.elinca.it Downlights

FLAT 4 - 30W	Optics	Output	ССТ	Part number
	90°	3428lm 3703lm 4114lm	2700K 3000K 4000K	D011.30W090□927 D011.30W090□930 D011.30W090□940
☐ refers to finishing: B: Black, W: White. Other CCT upon request.				

FLAT 4 - 40W	Optics	Output	ССТ	Part number
	90°	4898lm 5290lm 5878lm	2700K 3000K 4000K	D012.40W090□927 D012.40W090□930 D012.40W090□940
☐ refers to finishing: B: Black, W: White. Other CCT upon request.				

