

# FRAME 1



## Features

Displaying our FRAME 1, featuring a lumen output of 300lm to 420lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers zoomable beam angles ranging from 20÷35° to 25÷45° and framing feature, making it ideal for artwork lighting. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

## Dimming options

For dimmable version add the following suffix to the Part number → -DA: DALI.

## Applications

FRAME projectors provide focused, adjustable lightings specifically designed for precise framings of paintings and exhibits in museums and galleries. Their minimalist designs ensure consistent, glare-free illuminations that enhance artworks with true-to-life colours and fine details. Equipped with versatile mounting options and framing accessories, the systems allow exact light shaping and positioning for highlighting specific areas while protecting surrounding surfaces. Engineered for professional exhibitions, they deliver superior light qualities without compromising artwork integrity.



FRAME 1 - 10W	Optics	Output	CCT	Part number
	20÷35°	300lm	2700K	R019.10W2035□927
		324lm	3000K	R019.10W2035□930
		360lm	4000K	R019.10W2035□940
	25÷45°	350lm	2700K	R019.10W2545□927
		378lm	3000K	R019.10W2545□930
		420lm	4000K	R019.10W2545□940
□ refers to finishing: B: Black, W: White. Other CCT upon request.				