

# FRAME 3



## Features

Displaying our FRAME 3, featuring a lumen output of 350lm to 420lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This adaptable product offers a 15÷40° zoomable beam angle and framing feature, making it ideal for artwork lighting. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

## Dimming options

For dimmable version add the following suffix to the Part number → -DA: DALI.

## Applications

FRAME projectors provide focused, adjustable lightings specifically designed for precise framings of paintings and exhibits in museums and galleries. Their minimalist designs ensure consistent, glare-free illuminations that enhance artworks with true-to-life colours and fine details. Equipped with versatile mounting options and framing accessories, the systems allow exact light shaping and positioning for highlighting specific areas while protecting surrounding surfaces. Engineered for professional exhibitions, they deliver superior light qualities without compromising artwork integrity.



**FRAME 3 - 10W**

Optics	Output	CCT	Part number
15÷40°	350lm	2700K	R021.10W1540□927
	378lm	3000K	R021.10W1540□930
	420lm	4000K	R021.10W1540□940

□ refers to finishing:  
B: Black, W: White.  
Other CCT upon request.

**Accessories**

Description	Part number
Honeycomb	ACC01221
Soft light filter	ACC01222
Oval filter	ACC01223
Full snoot	ACC01224
Half snoot	ACC01225