

HALL 1



Features

Showcasing our HALL 1, featuring a lumen output of 899lm to 1086lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 30° to 75°, making it ideal for halls and corridors. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

HALL downlights are state-of-the-art solutions offering the perfect balance of visual comfort and luminous efficiency. Designed for high ceilings, they deliver impressive lumen output, making them ideal for retail spaces, offices, airports, and theatres. With powerful light output, they ensure every area is brightly lit. Whether you're creating a welcoming retail atmosphere, boosting productivity in an office, or setting the perfect ambiance in a theatre, HALL downlights are the ultimate choices for high-performance lighting that elevates any environment.



HALL 1 - 9W	Optics	Output	CCT	Part number
Other CCT upon request.	30°	905lm	2700K	A066.09W030W927
		977lm	3000K	A066.09W030W930
		1086lm	4000K	A066.09W030W940
	45°	901lm	2700K	A066.09W045W927
		973lm	3000K	A066.09W045W930
		1081lm	4000K	A066.09W045W940
	75°	899lm	2700K	A066.09W075W927
		971lm	3000K	A066.09W075W930
		1079lm	4000K	A066.09W075W940