

# IRIS 2



## Features

Showcasing our IRIS 2, featuring a lumen output of 1414lm to 1900lm. Available in static white, tunable white and dim-to warm, with additional options on request. This versatile product offers various beam angles ranging from 15° to 50°, making it ideal for museum and art gallery. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

## Dimming options

For dimmable version add the following suffix to the Part number → -DA: DALI.

## Applications

IRIS high-performance projectors are the top choices for luxury boutiques, delivering precise, high-quality lighting that enhances every detail. With comprehensive ranges of accessories, our track systems stand out as some of the most complete on the market, providing unmatched flexibility and reliability. Designed to adapt to diverse applications, they ensure seamless installations and consistent performances, making them the ideal solutions for sophisticated retail environments that demand both elegance and functionality.



**IRIS 2 - 20W - White**

	Optics	Output	CCT	Part number
 □ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	1584lm	2700K	R009.20W015□927
		1710lm	3000K	R009.20W015□930
		1900lm	4000K	R009.20W015□940
	24°	1577lm	2700K	R009.20W024□927
		1703lm	3000K	R009.20W024□930
		1893lm	4000K	R009.20W024□940
	36°	1577lm	2700K	R009.20W036□927
		1703lm	3000K	R009.20W036□930
		1893lm	4000K	R009.20W036□940
	50°	1571lm	2700K	R009.20W050□927
		1697lm	3000K	R009.20W050□930
		1885lm	4000K	R009.20W050□940

**IRIS 2 - 20W - Tunable white**

	Optics	Output	CCT	Part number
 □ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	1425lm	2700K	R010.20W015□CCT
		1767lm	6500K	
	24°	1420lm	2700K	R010.20W024□CCT
		1760lm	6500K	
	36°	1420lm	2700K	R010.20W036□CCT
		1760lm	6500K	
	50°	1414lm	2700K	R010.20W050□CCT
		1753lm	6500K	

**IRIS 2 - 20W - Dim to warm**

	Optics	Output	CCT	Part number
 □ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	1539lm	1800K-3000K	R011.20W015□DTW
	24°	1533lm	1800K-3000K	R011.20W024□DTW
	36°	1533lm	1800K-3000K	R011.20W036□DTW
	50°	1527lm	1800K-3000K	R011.20W050□DTW