

IRIS 3



Features

Showcasing our IRIS 3, featuring a lumen output of 2247lm to 3019lm. Available in static white, tunable white and dim-to warm, with additional options on request. This versatile product offers various beam angles ranging from 15° to 50°, making it ideal for museum and art gallery. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -DA: DALI.

Applications

IRIS high-performance projectors are the top choices for luxury boutiques, delivering precise, high-quality lighting that enhances every detail. With comprehensive ranges of accessories, our track systems stand out as some of the most complete on the market, providing unmatched flexibility and reliability. Designed to adapt to diverse applications, they ensure seamless installations and consistent performances, making them the ideal solutions for sophisticated retail environments that demand both elegance and functionality.



IRIS 3 - 30W - White

	Optics	Output	CCT	Part number
 □ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	2516lm	2700K	R012.30W015□927
		2717lm	3000K	R012.30W015□930
		3019lm	4000K	R012.30W015□940
	24°	2506lm	2700K	R012.30W024□927
		2706lm	3000K	R012.30W024□930
		3007lm	4000K	R012.30W024□940
	36°	2506lm	2700K	R012.30W036□927
		2706lm	3000K	R012.30W036□930
		3007lm	4000K	R012.30W036□940
	50°	2496lm	2700K	R012.30W050□927
		2695lm	3000K	R012.30W050□930
		2995lm	4000K	R012.30W050□940

IRIS 3 - 30W - Tunable white

	Optics	Output	CCT	Part number
 □ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	2265lm	2700K	R013.30W015□CCT
		2808lm	6500K	
	24°	2256lm	2700K	R013.30W024□CCT
		2797lm	6500K	
	36°	2256lm	2700K	R013.30W036□CCT
		2797lm	6500K	
	50°	2247lm	2700K	R013.30W050□CCT
		2786lm	6500K	

IRIS 3 - 30W - Dim to warm

	Optics	Output	CCT	Part number
 □ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	2446lm	1800K-3000K	R014.30W015□DTW
	24°	2436lm	1800K-3000K	R014.30W024□DTW
	36°	2436lm	1800K-3000K	R014.30W036□DTW
	50°	2426lm	1800K-3000K	R014.30W050□DTW