


LOOP 2



Light output: up to 2429lm **Cut out:** ø125mm **Standard finishing:** ● ○

Features

Presenting our LOOP 2, featuring a lumen output of 1619lm to 2429lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 18° to 50°, making it ideal for balconies and canopy. With an IP65 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

LOOP recessed outdoor downlights deliver superior glare control through recessed optics that maintain discreet, dark appearances from various viewing angles. These designs ensure visually comfortable environments, minimizing distractions and enhancing ambiance. Ideal for architectural facades, outdoor walkways, covered terraces, hotel entrances, and commercial spaces, LOOP combine performances and aesthetics to elevate any exterior lighting projects with elegance and precision.



IP65



CC
Constant
Current



LM80

SDCM
<3

CRI
>90



LOOP 2 - 20W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Standard configuration: W, white body, mirror silver reflector. Other CCT upon request.	18°	1632lm	2700K	D015.20W018□927
		1763lm	3000K	D015.20W018□930
		1959lm	4000K	D015.20W018□940
	24°	1626lm	2700K	D015.20W024□927
		1756lm	3000K	D015.20W024□930
		1951lm	4000K	D015.20W024□940
	36°	1626lm	2700K	D015.20W036□927
		1756lm	3000K	D015.20W036□930
		1951lm	4000K	D015.20W036□940
	50°	1619lm	2700K	D015.20W050□927
		1749lm	3000K	D015.20W050□930
		1943lm	4000K	D015.20W050□940

LOOP 2 - 25W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Standard configuration: W, white body, mirror silver reflector. Other CCT upon request.	18°	2024lm	2700K	D016.25W018□927
		2186lm	3000K	D016.25W018□930
		2429lm	4000K	D016.25W018□940
	24°	2016lm	2700K	D016.25W024□927
		2177lm	3000K	D016.25W024□930
		2419lm	4000K	D016.25W024□940
	36°	2016lm	2700K	D016.25W036□927
		2177lm	3000K	D016.25W036□930
		2419lm	4000K	D016.25W036□940
	50°	2008lm	2700K	D016.25W050□927
		2168lm	3000K	D016.25W050□930
		2409lm	4000K	D016.25W050□940

Accessories

	Description	Part number
	Matt black reflector	ACC01086
	Matt white reflector	ACC01087
	Mirror silver reflector	ACC01088
	Honeycomb	ACC01089
	Frosted glass	ACC01090