


LUMINA 2



Light output: up to 3203lm **Cut out:** ø130mm **Standard finishing:** ● ○

Features

Highlighting our LUMINA 2, featuring a lumen output of 1884lm to 3203lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This adaptable product offers a 60° beam angle, making it ideal for patios and courtyards. With an IP65 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

LUMINA ceiling recessed luminaires are specially designed to withstand outdoor conditions, featuring IP65 protection ratings on both the fronts and backs of the products. These make them ideal choices for illuminating the exteriors of properties, such as walkways, balconies, and patios. Not only do they enhance the designs of these spaces, but they also improve security and safety, offering reliable, high-performance lighting in any outdoor setting. With their durability and versatile applications, LUMINA luminaires add both style and functionality to your property.



LUMINA 2 - 15W**Optics****Output****CCT****Part number**

60°

1884lm
2035lm
2261lm2700K
3000K
4000KD002.15W060□927
D002.15W060□930
D002.15W060□940

□ refers to finishing:
B: Black, W: White.
Other CCT upon request.

LUMINA 2- 20W**Optics****Output****CCT****Part number**

60°

2670lm
2883lm
3203lm2700 K
3000 K
4000 KD003.20W060□927
D003.20W060□930
D003.20W060□940

□ refers to finishing:
B: Black, W: White.
Other CCT upon request.