LUMINA 3



Features

Highlighting our LUMINA 3, featuring a lumen output of 2670lm to 3203lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This adaptable product offers a 60° beam angle, making it ideal for patios and courtyards. With an IP65 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number \rightarrow -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

LUMINA ceiling recessed luminaires are specially designed to withstand outdoor conditions, featuring IP65 protection ratings on both the fronts and backs of the products. These make them ideal choices for illuminating the exteriors of properties, such as walkways, balconies, and patios. Not only do they enhance the designs of these spaces, but they also improve security and safety, offering reliable, high-performance lighting in any outdoor setting. With their durability and versatile applications, LUMINA luminaires add both style and functionality to your property.



























www.elinca.it Downlights

LUMINA 3 - 20W	Optics	Output	ССТ	Part number
	60°	2670lm 2883lm 3203lm	2700K 3000K 4000K	D004.20W060□927 D004.20W060□930 D004.20W060□940
☐ refers to finishing: B: Black, W: White. Other CCT upon request.				

