



OPUS 1



Light output: up to 837lm **Cut out:** 80x80mm **Standard finishing:** ● ○

Features

Introducing our OPUS 1, featuring a lumen output of 494lm to 837lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for office spaces. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

OPUS downlights are specifically designed to illuminate large commercial spaces and galleries. These fixtures deliver broad, even light distribution while maintaining excellent glare control, making them ideal for settings where visual comfort is a key point. Additionally, they ensure reliable, long-lasting performance, making them practical choices for any professional environment. Perfect for commercial spaces, retail displays, or exhibitions, OPUS enhances the overall atmosphere while effectively highlighting exhibits and products to create an engaging visual experiences.



OPUS 1 - 6W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	498lm	2700K	A090.06W015□927
		538lm	3000K	A090.06W015□930
		598lm	4000K	A090.06W015□940
	24°	496lm	2700K	A090.06W024□927
		536lm	3000K	A090.06W024□930
		595lm	4000K	A090.06W024□940
	35°	496lm	2700K	A090.06W035□927
		536lm	3000K	A090.06W035□930
		595lm	4000K	A090.06W035□940
	55°	494lm	2700K	A090.06W055□927
		534lm	3000K	A090.06W055□930
		593lm	4000K	A090.06W055□940

OPUS 1 - 9W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	697lm	2700K	A091.09W015□927
		753lm	3000K	A091.09W015□930
		837lm	4000K	A091.09W015□940
	24°	694lm	2700K	A091.09W024□927
		750lm	3000K	A091.09W024□930
		833lm	4000K	A091.09W024□940
	35°	694lm	2700K	A091.09W035□927
		750lm	3000K	A091.09W035□930
		833lm	4000K	A091.09W035□940
	55°	692lm	2700K	A091.09W055□927
		747lm	3000K	A091.09W055□930
		830lm	4000K	A091.09W055□940