


OUT 1



Light output: up to 837lm **Cut out:** ø75mm **Standard finishing:** ● ○

Features

Showcasing our OUT 1, featuring a lumen output of 494lm to 837lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for villa entrances. With an IP54 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

OUT series of outdoor downlights enhance ambient lightings in hospitality and residential settings. Designed for visual comfort, they feature recessed optics and the options for honeycomb louvres. With UGR of less than 19, these downlights are available in narrow, medium, and wide optics to suit various lighting needs. Whether creating welcoming atmospheres for guests or adding touches of elegance to residential spaces, OUT downlights deliver both high performances and aesthetic appeals for wide ranges of environments.



OUT 1 - 6W

| | Optics | Output | CCT | Part number |
|--|--------|--------|-------|-----------------|
| □ refers to finishing: B: Black, W: White. Other CCT upon request. | 15° | 498lm | 2700K | C001.06W015□927 |
| | | 538lm | 3000K | C001.06W015□930 |
| | | 598lm | 4000K | C001.06W015□940 |
| | 24° | 496lm | 2700K | C001.06W024□927 |
| | | 536lm | 3000K | C001.06W024□930 |
| | | 595lm | 4000K | C001.06W024□940 |
| | 35° | 496lm | 2700K | C001.06W035□927 |
| | | 536lm | 3000K | C001.06W035□930 |
| | | 595lm | 4000K | C001.06W035□940 |
| | 55° | 494lm | 2700K | C001.06W055□927 |
| | | 534lm | 3000K | C001.06W055□930 |
| | | 593lm | 4000K | C001.06W055□940 |

OUT 1 - 9W

| | Optics | Output | CCT | Part number |
|--|--------|--------|-------|-----------------|
| □ refers to finishing: B: Black, W: White. Other CCT upon request. | 15° | 697lm | 2700K | C002.09W015□927 |
| | | 753lm | 3000K | C002.09W015□930 |
| | | 837lm | 4000K | C002.09W015□940 |
| | 24° | 694lm | 2700K | C002.09W024□927 |
| | | 750lm | 3000K | C002.09W024□930 |
| | | 833lm | 4000K | C002.09W024□940 |
| | 35° | 694lm | 2700K | C002.09W035□927 |
| | | 750lm | 3000K | C002.09W035□930 |
| | | 833lm | 4000K | C002.09W035□940 |
| | 55° | 692lm | 2700K | C002.09W055□927 |
| | | 747lm | 3000K | C002.09W055□930 |
| | | 830lm | 4000K | C002.09W055□940 |