SEAL 2



Features

Showcasing our SEAL 2, featuring a lumen output of 2055lm to 2983lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 18° to 50°, making it ideal for outdoor living areas. With an IP65 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

SEAL recessed outdoor downlights offer comfortable light emissions and ensure good visual comfort from multiple viewing angles, making them ideal for outdoor architectural lighting. Their discreet designs blend seamlessly into any facades or structures, providing uniform illumination without glare. Perfect for pathways, building entrances, terraces, staircases, and public spaces, SEAL enhance both safety and aesthetics in residential, commercial, and hospitality environments.

























www.elinca.it Downlights

SEAL 2 - 20W	Optics	Output	ССТ	Part number
	18°	2072lm	2700K	D021.20W018□927
		2237lm	3000K	D021.20W018□930
		2486lm	4000K	D021.20W018□940
	24°	2063lm	2700K	D021.20W024□927
		2228lm	3000K	D021.20W024□930
		2476lm	4000K	D021.20W024□940
	36°	2063lm	2700K	D021.20W036□927
		2228lm	3000K	D021.20W036□930
☐ refers to finishing: B: Black, W: White. Standard configuration: W, white body, mirror silver reflector. Other CCT upon request.		2476lm	4000K	D021.20W036□940
	50°	2055lm	2700K	D021.20W050□927
		2219lm	3000K	D021.20W050□930
		2466lm	4000K	D021.20W050□940

SEAL 2 - 25W	Optics	Output	ССТ	Part number
	18°	2486lm	2700K	D022.25W018□927
		2685lm	3000K	D022.25W018□930
		2983lm	4000K	D022.25W018□940
	24°	2476lm	2700K	D022.25W024□927
		2674lm	3000K	D022.25W024□930
		2971lm	4000K	D022.25W024□940
	36°	2476lm	2700K	D022.25W036□927
		2674lm	3000K	D022.25W036□930
☐ refers to finishing:		2971lm	4000K	D022.25W036□940
B: Black, W: White.	50°	2466lm	2700K	D022.25W050□927
Standard configuration:		2663lm	3000K	D022.25W050□930
W, white body, mirror silver reflector. Other CCT upon request.		2959lm	4000K	D022.25W050□940

Accessories	Description	Part number
	Matt black reflector	ACC01175
	Matt white reflector	ACC01176
	Mirror silver reflector	ACC01177
	Honeycomb	ACC01178
	Frosted glass	ACC01179

