


SPOT-R 1



Light output: up to 837lm **Cut out:** ø75mm **Standard finishing:** ● ○

Features

Showcasing our SPOT-R 1, featuring a lumen output of 494lm to 837lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for commercial location. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

SPOT-R downlights are the ideal combination of simplicity, durability, and functionality with our downlights, perfectly suited for all your general lighting needs. Whether you require efficient illumination for expansive spaces, sleek lighting solutions for retail environments, or optimal settings for meeting rooms, these downlights are designed to deliver it. They provide effective, uniform lighting while minimizing visual impact, allowing them to integrate seamlessly into any environment. Ideal for offices, commercial spaces, and public areas, these downlights offer reliable and enduring lighting solutions.



























SPOT-R 1 - 6W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	498lm	2700K	A026.06W015□927
		538lm	3000K	A026.06W015□930
		598lm	4000K	A026.06W015□940
	24°	496lm	2700K	A026.06W024□927
		536lm	3000K	A026.06W024□930
		595lm	4000K	A026.06W024□940
	35°	496lm	2700K	A026.06W035□927
		536lm	3000K	A026.06W035□930
		595lm	4000K	A026.06W035□940
	55°	494lm	2700K	A026.06W055□927
		534lm	3000K	A026.06W055□930
		593lm	4000K	A026.06W055□940

SPOT-R 1 - 9W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	697lm	2700K	A027.09W015□927
		753lm	3000K	A027.09W015□930
		837lm	4000K	A027.09W015□940
	24°	694lm	2700K	A027.09W024□927
		750lm	3000K	A027.09W024□930
		833lm	4000K	A027.09W024□940
	35°	694lm	2700K	A027.09W035□927
		750lm	3000K	A027.09W035□930
		833lm	4000K	A027.09W035□940
	55°	692lm	2700K	A027.09W055□927
		747lm	3000K	A027.09W055□930
		830lm	4000K	A027.09W055□940

Accessories

	Description	Part number
	Frosted glass	ACC01185