


SPOT-R 4



Light output: up to 3108lm **Cut out:** ø125mm **Standard finishing:** ● ○

Features

Showcasing our SPOT-R 4, featuring a lumen output of 2569lm to 3108lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for commercial location. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

SPOT-R downlights are the ideal combination of simplicity, durability, and functionality with our downlights, perfectly suited for all your general lighting needs. Whether you require efficient illumination for expansive spaces, sleek lighting solutions for retail environments, or optimal settings for meeting rooms, these downlights are designed to deliver it. They provide effective, uniform lighting while minimizing visual impact, allowing them to integrate seamlessly into any environment. Ideal for offices, commercial spaces, and public areas, these downlights offer reliable and enduring lighting solutions.



SPOT-R 4 - 28W

	Optics	Output	CCT	Part number
<div> <div></div> <div> □ refers to finishing: B: Black, W: White. Other CCT upon request. </div> </div>	15°	2590lm	2700K	A031.28W015□927
		2797lm	3000K	A031.28W015□930
		3108lm	4000K	A031.28W015□940
	24°	2579lm	2700K	A031.28W024□927
		2786lm	3000K	A031.28W024□930
		3095lm	4000K	A031.28W024□940
	35°	2579lm	2700K	A031.28W035□927
		2786lm	3000K	A031.28W035□930
		3095lm	4000K	A031.28W035□940
	55°	2569lm	2700K	A031.28W055□927
		2774lm	3000K	A031.28W055□930
		3083lm	4000K	A031.28W055□940

Accessories

Description	Part number
Frosted glass	ACC01188