


SPOT-SQ 2



Light output: up to 1554lm **Cut out:** 75x75mm **Standard finishing:** ● ○

Features

Highlighting our SPOT-SQ 2, featuring a lumen output of 988lm to 1554lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for commercial spaces. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

SPOT-SQ downlights are the ideal combination of simplicity, durability, and functionality with our downlights, perfectly suited for all your general lighting needs. Whether you require efficient illumination for expansive spaces, sleek lighting solutions for retail environments, or optimal settings for meeting rooms, these downlights are designed to deliver it. They provide effective, uniform lighting while minimizing visual impact, allowing them to integrate seamlessly into any environment. Ideal for offices, commercial spaces, and public areas, these downlights offer reliable and enduring lighting solutions.



SPOT-SQ 2 - 12W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	996lm	2700K	A035.12W015□927
		1076lm	3000K	A035.12W015□930
		1195lm	4000K	A035.12W015□940
	24°	992lm	2700K	A035.12W024□927
		1071lm	3000K	A035.12W024□930
		1190lm	4000K	A035.12W024□940
	35°	992lm	2700K	A035.12W035□927
		1071lm	3000K	A035.12W035□930
		1190lm	4000K	A035.12W035□940
	55°	988lm	2700K	A035.12W055□927
		1067lm	3000K	A035.12W055□930
		1186lm	4000K	A035.12W055□940

SPOT-SQ 2 - 15W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	1295lm	2700K	A036.15W015□927
		1398lm	3000K	A036.15W015□930
		1554lm	4000K	A036.15W015□940
	24°	1290lm	2700K	A036.15W024□927
		1393lm	3000K	A036.15W024□930
		1548lm	4000K	A036.15W024□940
	35°	1290lm	2700K	A036.15W035□927
		1393lm	3000K	A036.15W035□930
		1548lm	4000K	A036.15W035□940
	55°	1284lm	2700K	A036.15W055□927
		1381lm	3000K	A036.15W055□930
		1541lm	4000K	A036.15 W055□940

Accessories

	Description	Part number
	Frosted glass	ACC01191