

APEX 4



Features

Introducing our APEX 4, featuring a lumen output of 2843lm to 3862lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product features two adjustable beam angles, ranging from 24° to 50°, making it ideal for trendy outdoor restaurant. With an IP65 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Applications

APEX surface-mounted outdoor downlights combine durability, style, and functionality, delivering focused illumination with sleek designs. Easy to install, they adapt seamlessly to various outdoor environments, making them ideal for entrances, covered walkways, terraces, patios, and building facades. Their robust constructions ensure reliable performance in all weather conditions, enhancing safety and ambiance while maintaining modern, clean aesthetics that complement any architectural style or outdoor setting.

IP65

DRIVER INCLUDED

CC
Constant
Current

LM80

SDCM
<3

CRI
>90

3
YEARS
WARRANTY

APEX 4 - 25W

Optics	Output	CCT	Part number
24°	2855lm	2700K	I007.25W024□927
	3083lm	3000K	I007.25W024□930
	3426lm	4000K	I007.25W024□940
50°	2843lm	2700K	I007.25W050□927
	3071lm	3000K	I007.25W050□930
	3412lm	4000K	I007.25W050□940

□ refers to finishing:
 B: Black, W: White.
 Standard configuration:
 W, white body, mirror silver reflector.
 Other CCT upon request.

APEX 4 - 30W

Optics	Output	CCT	Part number
24°	3218lm	2700K	I008.30W024□927
	3475lm	3000K	I008.30W024□930
	3862lm	4000K	I008.30W024□940
50°	3205lm	2700K	I008.30W050□927
	3461lm	3000K	I008.30W050□930
	3846lm	4000K	I008.30W050□940

□ refers to finishing:
 B: Black, W: White.
 Standard configuration:
 W, white body, mirror silver reflector.
 Other CCT upon request.

Accessories

Description	Part number
Matt black reflector	ACC01060
Matt white reflector	ACC01061
Mirror silver reflector	ACC01062