


DIRECT 3



Light output: up to 1524lm **Cut out:** ø60mm **Standard finishing:** ● ○

Features

Highlighting our DIRECT 3, featuring a lumen output of 1260lm to 1524lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 60°, making it ideal for hotel spaces and galleries. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

DIRECT ceiling-mounted projectors are designed with simple and minimalist aesthetics to fit either hotel spaces or high-end retail shops. Their essential designs seamlessly integrate into any environment, while their adjustable features ensure precise and customizable lighting. Perfect for hotel spaces and galleries, for high-end retail shops and exhibitions, DIRECT offers both style and functionality, providing the ideal lighting solutions for premium interiors.



DIRECT 3 - 15W

Optics	Output	CCT	Part number
--------	--------	-----	-------------

<div> <div></div> <div>□ refers to finishing: B: Black, W: White. Other CCT upon request.</div> </div>	15°	1270lm	2700K	A114.15W015□927
		1371lm	3000K	A114.15W015□930
		1524lm	4000K	A114.15W015□940
	24°	1265lm	2700K	A114.15W024□927
		1366lm	3000K	A114.15W024□930
		1518lm	4000K	A114.15W024□940
	38°	1261lm	2700K	A114.15W038□927
		1362lm	3000K	A114.15W038□930
		1513lm	4000K	A114.15W038□940
	60°	1260lm	2700K	A114.15W060□927
		1360lm	3000K	A114.15W060□930
		1512lm	4000K	A114.15W060□940