


DIRECT 4



Features

Highlighting our DIRECT 4, featuring a lumen output of 1659lm to 2007lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 60°, making it ideal for hotel spaces and galleries. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

DIRECT ceiling-mounted projectors are designed with simple and minimalist aesthetics to fit either hotel spaces or high-end retail shops. Their essential designs seamlessly integrate into any environment, while their adjustable features ensure precise and customizable lighting. Perfect for hotel spaces and galleries, for high-end retail shops and exhibitions, DIRECT offers both style and functionality, providing the ideal lighting solutions for premium interiors.



























DIRECT 4 - 20W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	1672lm	2700K	A115.20W015□927
		1806lm	3000K	A115.20W015□930
		2007lm	4000K	A115.20W015□940
	24°	1666lm	2700K	A115.20W024□927
		1799lm	3000K	A115.20W024□930
		1999lm	4000K	A115.20W024□940
	38°	1661lm	2700K	A115.20W038□927
		1793lm	3000K	A115.20W038□930
		1993lm	4000K	A115.20W038□940
	60°	1659lm	2700K	A115.20W060□927
		1792lm	3000K	A115.20W060□930
		1991lm	4000K	A115.20W060□940