


# DIRECT 5



**Light output:** up to 3133lm    **Cut out:** ø75mm    **Standard finishing:** ● ○

## Features

Highlighting our DIRECT 5, featuring a lumen output of 2590lm to 3133lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 60°, making it ideal for hotel spaces and galleries. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

## Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

## Applications

DIRECT ceiling-mounted projectors are designed with simple and minimalist aesthetics to fit either hotel spaces or high-end retail shops. Their essential designs seamlessly integrate into any environment, while their adjustable features ensure precise and customizable lighting. Perfect for hotel spaces and galleries, for high-end retail shops and exhibitions, DIRECT offers both style and functionality, providing the ideal lighting solutions for premium interiors.



**DIRECT 5 - 30W**

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	2611lm	2700K	A116.30W015□927
		2819lm	3000K	A116.30W015□930
		3133lm	4000K	A116.30W015□940
	24°	2600lm	2700K	A116.30W024□927
		2808lm	3000K	A116.30W024□930
		3120lm	4000K	A116.30W024□940
	38°	2592lm	2700K	A116.30W038□927
		2800lm	3000K	A116.30W038□930
		3111lm	4000K	A116.30W038□940
	60°	2590lm	2700K	A116.30W060□927
		2797lm	3000K	A116.30W060□930
		3107lm	4000K	A116.30W060□940