

FRAME 2



Features

Displaying our FRAME 2, featuring a lumen output of 850lm to 1140lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers zoomable beam angles ranging from 15÷25° to 20÷36° and framing feature, making it ideal for artwork lighting. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -DA: DALI.

Applications

FRAME projectors provide focused, adjustable lightings specifically designed for precise framings of paintings and exhibits in museums and galleries. Their minimalist designs ensure consistent, glare-free illuminations that enhance artworks with true-to-life colours and fine details. Equipped with versatile mounting options and framing accessories, the systems allow exact light shaping and positioning for highlighting specific areas while protecting surrounding surfaces. Engineered for professional exhibitions, they deliver superior light qualities without compromising artwork integrity.

IP20

AC
240V

Dimmable

LM80

SDCM
<2

CRI
>95

SHAPE

ZOOM

FRAME 2 - 28W	Optics	Output	CCT	Part number
	15÷25°	850lm	2700K	R020.28W1525□927
		918lm	3000K	R020.28W1525□930
		1020lm	4000K	R020.28W1525□940
	20÷36°	950lm	2700K	R020.28W2036□927
		1026lm	3000K	R020.28W2036□930
		1140lm	4000K	R020.28W2036□940
□ refers to finishing: B: Black, W: White. Other CCT upon request.				