

FRAME 3



Features

Displaying our FRAME 3, featuring a lumen output of 350lm to 420lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This adaptable product offers a 15÷40° zoomable beam angle and framing feature, making it ideal for artwork lighting. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -DA: DALI.

Applications

FRAME projectors provide focused, adjustable lightings specifically designed for precise framings of paintings and exhibits in museums and galleries. Their minimalist designs ensure consistent, glare-free illuminations that enhance artworks with true-to-life colours and fine details. Equipped with versatile mounting options and framing accessories, the systems allow exact light shaping and positioning for highlighting specific areas while protecting surrounding surfaces. Engineered for professional exhibitions, they deliver superior light qualities without compromising artwork integrity.



IP20

AC 240V

 Dimmable

LM80

SDCM <2

CRI >95

SHAPE

ZOOM

CE

 RoHS

 Reach

 ETL US

3 YEARS WARRANTY

FRAME 3 - 10W**Optics****Output****CCT****Part number**

15÷40°

350lm

2700K

R021.10W1540□927

378lm

3000K

R021.10W1540□930

420lm

4000K

R021.10W1540□940

□ refers to finishing:
B: Black, W: White.
Other CCT upon request.

Accessories**Description****Part number**

Honeycomb

ACC01221

Soft light filter

ACC01222

Oval filter

ACC01223

Full snoot

ACC01224

Half snoot

ACC01225