


IRIS-Z 2



Light output: up to 2652lm **Standard finishing:** ● ○

Features

Highlighting our IRIS-Z 2, featuring a lumen output of 2210lm to 2652lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This adaptable product offers a 22÷57° zoomable beam angle, making it ideal for museum and art gallery. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -DA: DALI.

Applications

IRIS-Z premium zoom projectors are the ideal choices for galleries and museums, offering high-performance lighting with adjustable beam angles for precise focus on artworks and exhibits. Designed for maximum flexibility, they adapt to changing display needs while maintaining exceptional visual quality. Paired with our comprehensive track systems and accessories, they provide seamless integration, reliable performance, and refined control, making them perfect for sophisticated cultural spaces that demand both precision and discretion.



IRIS-Z 2 - 30W	Optics	Output	CCT	Part number
	22÷57°	2210lm	2700K	R018.30W2257□927
		2387lm	3000K	R018.30W2257□930
		2652lm	4000K	R018.30W2257□940
<div>□ refers to finishing: B: Black, W: White. Other CCT upon request.</div>				