
LOOK-D 1



Features

Highlighting our LOOK-D 1, featuring a lumen output of 988lm to 1673lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for luxury hotel lobbies. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

LOOK-D double head adjustable downlights are designed to be fitted discreetly within the ENDLESS recessed ceiling channels, offering sleek, minimalist looks ideal for premium interiors. Their subtle designs blend seamlessly into hotel lobbies, luxury retail spaces, galleries, and exhibitions. With two adjustable heads each, they provide versatile, precise illumination, combining functionality with refined aesthetics. These high-end lighting solutions enhance any environment while remaining elegantly unobtrusive.





























| LOOK-D 1 - 12W (2x6W) | Optics | Output | ССТ | Part number |
|---|--------|--------|-------|-----------------|
| | 15° | 996lm | 2700K | R041.12W015□927 |
| | | 1076lm | 3000K | R041.12W015□930 |
| | | 1195lm | 4000K | R041.12W015□940 |
| | 24° | 992lm | 2700K | R041.12W024□927 |
| | | 1071lm | 3000K | R041.12W024□930 |
| | | 1190lm | 4000K | R041.12W024□940 |
| | 35° | 992lm | 2700K | R041.12W035□927 |
| | | 1071lm | 3000K | R041.12W035□930 |
| | | 1190lm | 4000K | R041.12W035□940 |
| | 55° | 988lm | 2700K | R041.12W055□927 |
| ☐ refers to finishing: | | 1067lm | 3000K | R041.12W055□930 |
| B: Black, W: White. Other CCT upon request. | | 1186lm | 4000K | R041.12W055□940 |

| LOOK-D 1 - 18W (2x9W) | Optics | Output | ССТ | Part number |
|---|--------|--------|-------|-----------------|
| | 15° | 1394lm | 2700K | R042.18W015□927 |
| | | 1506lm | 3000K | R042.18W015□930 |
| | | 1673lm | 4000K | R042.18W015□940 |
| | 24° | 1389lm | 2700K | R042.18W024□927 |
| | | 1500lm | 3000K | R042.18W024□930 |
| | | 1667lm | 4000K | R042.18W024□940 |
| | 35° | 1389lm | 2700K | R042.18W035□927 |
| | | 1500lm | 3000K | R042.18W035□930 |
| | | 1667lm | 4000K | R042.18W035□940 |
| | 55° | 1383lm | 2700K | R042.18W055□927 |
| ☐ refers to finishing: | | 1494lm | 3000K | R042.18W055□930 |
| B: Black, W: White. Other CCT upon request. | | 1660lm | 4000K | R042.18W055□940 |

| Accessories | Description | Part number |
|-------------|------------------------------|-------------|
| | Adapting plate for 75mm cut | ACC01217 |
| | Adapting plate for 145mm cut | ACC01218 |
| | Honeycomb set | ACC01219 |
| | | |
| | | |
| | | |
| | | |
| | | |

