


LOOK-S 1



Light output: up to 837lm **Standard finishing:** ● ○

Features


Showcasing our LOOK-S 1, featuring a lumen output of 494lm to 837lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for luxury retail spaces. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

LOOK-S adjustable downlights are designed to be recessed discreetly within the ENDLESS ceiling channels, delivering clean, minimalist looks perfect for premium interiors. Their subtle designs blend seamlessly into hotel lobbies, luxury retail spaces, galleries, and exhibitions. With adjustable light heads, they provide precise, customizable illumination, combining functionality with refined aesthetics. These high-end lighting solutions enhance the environments while remaining elegantly unobtrusive.



LOOK-S 1 - 6W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	498lm	2700K	R037.06W015□927
		538lm	3000K	R037.06W015□930
		598lm	4000K	R037.06W015□940
	24°	496lm	2700K	R037.06W024□927
		536lm	3000K	R037.06W024□930
		595lm	4000K	R037.06W024□940
	35°	496lm	2700K	R037.06W035□927
		536lm	3000K	R037.06W035□930
		595lm	4000K	R037.06W035□940
	55°	494lm	2700K	R037.06W055□927
		534lm	3000K	R037.06W055□930
		593lm	4000K	R037.06W055□940

LOOK-S 1 - 9W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	697lm	2700K	R038.09W015□927
		753lm	3000K	R038.09W015□930
		837lm	4000K	R038.09W015□940
	24°	694lm	2700K	R038.09W024□927
		750lm	3000K	R038.09W024□930
		833lm	4000K	R038.09W024□940
	35°	694lm	2700K	R038.09W035□927
		750lm	3000K	R038.09W035□930
		833lm	4000K	R038.09W035□940
	55°	692lm	2700K	R038.09W055□927
		747lm	3000K	R038.09W055□930
		830lm	4000K	R038.09W055□940

Accessories

	Description	Part number
	Adapting plate for 75mm cut	ACC01142
	Adapting plate for 145mm cut	ACC01143
	Honeycomb	ACC01144