LUMINA 1



Features

Highlighting our LUMINA 1, featuring a lumen output of 1018lm to 1221lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This adaptable product offers a 60° beam angle, making it ideal for patios and courtyards. With an IP65 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number \rightarrow -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

LUMINA ceiling recessed luminaires are specially designed to withstand outdoor conditions, featuring IP65 protection ratings on both the fronts and backs of the products. These make them ideal choices for illuminating the exteriors of properties, such as walkways, balconies, and patios. Not only do they enhance the designs of these spaces, but they also improve security and safety, offering reliable, high-performance lighting in any outdoor setting. With their durability and versatile applications, LUMINA luminaires add both style and functionality to your property.

























| LUMINA 1 - 9W | Optics | Output | ССТ | Part number |
|--|--------|----------------------------|-------------------------|---|
| | 60° | 1018lm 1099lm 1221lm | 2700K 3000K 4000K | D001.09W060□927 D001.09W060□930 D001.09W060□940 |
| | | | | |
| | | | | |
| ☐ refers to finishing: B: Black, W: White. Other CCT upon request. | | | | |

