

# LUXE-R 3



## Features

Highlighting our LUXE-R 3, featuring a lumen output of 988lm to 1554lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for lively public interiors. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

## Applications

LUXE-R are surface-mounted downlights that combine functionality and style, making them suitable for any environment. Designed for easy installation, they eliminate the need for recessed housings, ensuring seamless integrations. Their elegant, minimalist designs provide focused illuminations while enhancing the overall aesthetics of the spaces. Versatile and adaptable, LUXE-R are perfect for a wide range of settings, from contemporary restaurants to vibrant public interiors. They blend with different styles and contexts, ensuring your lighting designs is both functional and visually appealing.



**LUXE-R 3 - 12W**

|  | Optics | Output | CCT   | Part number     |
|--|--------|--------|-------|-----------------|
| □ refers to finishing:<br>B: Black, W: White.<br>Standard configuration:<br>W, white body, black reflector.<br>Other CCT upon request. | 15°    | 996lm  | 2700K | F005.12W015□927 |
|  |        | 1076lm | 3000K | F005.12W015□930 |
|  |        | 1195lm | 4000K | F005.12W015□940 |
|  | 24°    | 992lm  | 2700K | F005.12W024□927 |
|  |        | 1071lm | 3000K | F005.12W024□930 |
|  |        | 1190lm | 4000K | F005.12W024□940 |
|  | 35°    | 992lm  | 2700K | F005.12W035□927 |
|  |        | 1071lm | 3000K | F005.12W035□930 |
|  |        | 1190lm | 4000K | F005.12W035□940 |
|  | 55°    | 988lm  | 2700K | F005.12W055□927 |
|  |        | 1067lm | 3000K | F005.12W055□930 |
|  |        | 1186lm | 4000K | F005.12W055□940 |

**LUXE-R 3 - 15W**

|  | Optics | Output | CCT   | Part number     |
|--|--------|--------|-------|-----------------|
| □ refers to finishing:<br>B: Black, W: White.<br>Standard configuration:<br>W, white body, black reflector.<br>Other CCT upon request. | 15°    | 1295lm | 2700K | F006.15W015□927 |
|  |        | 1398lm | 3000K | F006.15W015□930 |
|  |        | 1554lm | 4000K | F006.15W015□940 |
|  | 24°    | 1290lm | 2700K | F006.15W024□927 |
|  |        | 1393lm | 3000K | F006.15W024□930 |
|  |        | 1548lm | 4000K | F006.15W024□940 |
|  | 35°    | 1290lm | 2700K | F006.15W035□927 |
|  |        | 1393lm | 3000K | F006.15W035□930 |
|  |        | 1548lm | 4000K | F006.15W035□940 |
|  | 55°    | 1284lm | 2700K | F006.15W055□927 |
|  |        | 1381lm | 3000K | F006.15W055□930 |
|  |        | 1541lm | 4000K | F006.15W055□940 |

**Accessories**

| Description          | Part number |
|----------------------|-------------|
| Matt black reflector | ACC01104    |
| Matt white reflector | ACC01105    |
| Honeycomb            | ACC01106    |