

LUXE-R 4



Features

Highlighting our LUXE-R 4, featuring a lumen output of 1729lm to 2092lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 50°, making it ideal for lively public interiors. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Applications

LUXE-R are surface-mounted downlights that combine functionality and style, making them suitable for any environment. Designed for easy installation, they eliminate the need for recessed housings, ensuring seamless integrations. Their elegant, minimalist designs provide focused illuminations while enhancing the overall aesthetics of the spaces. Versatile and adaptable, LUXE-R are perfect for a wide range of settings, from contemporary restaurants to vibrant public interiors. They blend with different styles and contexts, ensuring your lighting designs is both functional and visually appealing.



LUXE-R 4 - 20W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Standard configuration: W, white body, black reflector. Other CCT upon request.	15°	1743lm	2700K	F007.20W015□927
		1883lm	3000K	F007.20W015□930
		2092lm	4000K	F007.20W015□940
	24°	1736lm	2700K	F007.20W024□927
		1875lm	3000K	F007.20W024□930
		2083lm	4000K	F007.20W024□940
	35°	1736lm	2700K	F007.20W035□927
		1875lm	3000K	F007.20W035□930
		2083lm	4000K	F007.20W035□940
	50°	1729lm	2700K	F007.20W050□927
		1867lm	3000K	F007.20W050□930
		2075lm	4000K	F007.20W050□940

Accessories

Description	Part number
Matt black reflector	ACC01107
Matt white reflector	ACC01108
Honeycomb	ACC01109