


LUXE-SQ 5



Light output: up to 3108lm **Standard finishing:** ● ○

Features

Presenting our LUXE-SQ 5, featuring a lumen output of 2569lm to 3108lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 50°, making it ideal for lively public spaces. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Applications

LUXE-SQ are surface-mounted downlights that combine functionality and style, making them suitable for any environment. Designed for easy installation, they eliminate the need for recessed housing, ensuring seamless integration. Their elegant, minimalist designs provide focused illumination while enhancing the overall aesthetics of the spaces. Versatile and adaptable, LUXE-SQ are perfect for a wide range of settings, from contemporary restaurants to vibrant public interiors. They blend with different styles and contexts, ensuring your lighting designs are both functional and visually appealing.



IP20



CC
Constant
Current

LM80

SDCM
<3

CRI
>90



3
YEARS
WARRANTY

LUXE-SQ 5 - 28W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Standard configuration: W, white body, black reflector. Other CCT upon request.	15°	2590lm	2700K	F015.28W015□927
		2797lm	3000K	F015.28W015□930
		3108lm	4000K	F015.28W015□940
	24°	2579lm	2700K	F015.28W024□927
		2786lm	3000K	F015.28W024□930
		3095lm	4000K	F015.28W024□940
	35°	2579lm	2700K	F015.28W035□927
		2786lm	3000K	F015.28W035□930
		3095lm	4000K	F015.28W035□940
	50°	2569lm	2700K	F015.28W050□927
		2774lm	3000K	F015.28W050□930
		3083lm	4000K	F015.28W050□940

Accessories

	Description	Part number
	Matt black reflector	ACC01135
	Matt white reflector	ACC01136
	Honeycomb	ACC01137