

# M-HEAD 1



## Features

Introducing our M-HEAD 1, featuring a lumen output of 1760lm to 2198lm. Available in static white and tunable white, with additional options on request. This versatile product offers a unique movable axis feature, making it a premium choice for adaptive settings in high-ceilinged areas, with available beam angles ranging from 15° to 40°. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

## Dimming options

For DALI dimmable version add the following suffix to the Part number → -DA: DALI.

## Applications

M-HEAD motorized high-performance projectors are the premier choices for art galleries and luxury boutiques, delivering precise, dynamic lighting that highlights every detail with exceptional clarity. Equipped with advanced motorized tilts and pans, they offer effortless, remote adjustments for perfect illumination of artworks and displays. Supported by comprehensive accessory ranges, the systems ensure unmatched flexibility, seamless installations, and consistent performances, ideal for sophisticated environments demanding elegance, adaptability, and precision lighting control.

 IP20

 AC 240V

 Dimmable

 LM80

 SDCM <3

 CRI >90

 CASAMBI

 MOTORIZED













M-HEAD 1 - 20W - White	Optics	Output	CCT	Part number
<div><div></div><div>□ refers to finishing: B: Black, W: White. Other CCT upon request.</div></div>	15°	1773lm	2700K	R023.20W015□927-CA
		1915lm	3000K	R023.20W015□930-CA
		2127lm	4000K	R023.20W015□940-CA
	24°	1766lm	2700K	R023.20W024□927-CA
		1907lm	3000K	R023.20W024□930-CA
		2119lm	4000K	R023.20W024□940-CA
	40°	1760lm	2700K	R023.20W040□927-CA
		1901lm	3000K	R023.20W040□930-CA
		2113lm	4000K	R023.20W040□940-CA

M-HEAD 1 - 20W - Tunable white	Optics	Output	CCT	Part number
<div><div></div><div>□ refers to finishing: B: Black, W: White. Other CCT upon request.</div></div>	15°	1773lm	2700K	R024.20W015□CCT-CA
		2198lm	6500K	
	24°	1766lm	2700K	R024.20W024□CCT-CA
		2190lm	6500K	
	40°	1760lm	2700K	R024.20W040□CCT-CA
		2183lm	6500K	