M-HEAD 3



Features

Introducing our M-HEAD 3, featuring a lumen output of 1672lm to 2088lm. Available in static white and tunable white, with additional options on request. This versatile product offers a unique movable axis feature, making it a premium choice for adaptive settings in high-ceilinged areas, with available beam angles ranging from 15° to 40°. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For DALI dimmable version add the following suffix to the Part number \rightarrow -DA: DALI.

Applications

M-HEAD motorized high-performance projectors are the premier choices for art galleries and luxury boutiques, delivering precise, dynamic lighting that highlights every detail with exceptional clarity. Equipped with advanced motorized tilts and pans, they offer effortless, remote adjustments for perfect illumination of artworks and displays. Supported by comprehensive accessory ranges, the systems ensure unmatched flexibility, seamless installations, and consistent performances, ideal for sophisticated environments demanding elegance, adaptability, and precision lighting control.



























M-HEAD 3 - 20W - White	Optics	Output	ССТ	Part number
	15°	1684lm	2700K	R027.20W015□927-CA
		1819lm	3000K	R027.20W015□930-CA
		2021lm	4000K	R027.20W015□940-CA
	24°	1677lm	2700K	R027.20W024□927-CA
		1812lm	3000K	R027.20W024□930-CA
		2013lm	4000K	R027.20W024□940-CA
	40°	1672lm	2700K	R027.20W040□927-CA
		1806lm	3000K	R027.20W040□930-CA
		2007lm	4000K	R027.20W040□940-CA
☐ refers to finishing: B: Black, W: White. Other CCT upon request.				
other our apon request.				

M-HEAD 3 - 20W - Tunable white	Optics	Output	ССТ	Part number
	15°	1684lm 2088lm	2700K 6500K	R028.20W015□CCT-CA
	24°	1677lm 2080lm	2700K 6500K	R028.20W024□CCT-CA
	40°	1672lm 2074lm	2700K 6500K	R028.20W040□CCT-CA
□ refere to finishing:				
☐ refers to finishing: B: Black, W: White. Other CCT upon request.				

