


# OPUS 4



**Light output:** up to 3108lm   **Cut out:** 115x115mm   **Standard finishing:** ● ○

## Features

Introducing our OPUS 4, featuring a lumen output of 2569lm to 3108lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for office spaces. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

## Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

## Applications

OPUS downlights are specifically designed to illuminate large commercial spaces and galleries. These fixtures deliver broad, even light distribution while maintaining excellent glare control, making them ideal for settings where visual comfort is a key point. Additionally, they ensure reliable, long-lasting performance, making them practical choices for any professional environment. Perfect for commercial spaces, retail displays, or exhibitions, OPUS enhances the overall atmosphere while effectively highlighting exhibits and products to create an engaging visual experiences.



OPUS 4 - 28W	Optics	Output	CCT	Part number
<div>□ refers to finishing: B: Black, W: White. Other CCT upon request.</div>	15°	2590lm	2700K	A094.28W015□927
		2797lm	3000K	A094.28W015□930
		3108lm	4000K	A094.28W015□940
	24°	2579lm	2700K	A094.28W024□927
		2786lm	3000K	A094.28W024□930
		3095lm	4000K	A094.28W024□940
	35°	2579lm	2700K	A094.28W035□927
		2786lm	3000K	A094.28W035□930
		3095lm	4000K	A094.28W035□940
	55°	2569lm	2700K	A094.28W055□927
		2774lm	3000K	A094.28W055□930
		3083lm	4000K	A094.28W055□940