


OUT 1



Light output: up to 837lm **Cut out:** ø75mm **Standard finishing:** ● ○

Features

Showcasing our OUT 1, featuring a lumen output of 494lm to 837lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for villa entrances. With an IP54 rating, it provides suitable protection for outdoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

OUT series of outdoor downlights enhance ambient lightings in hospitality and residential settings. Designed for visual comfort, they feature recessed optics and the options for honeycomb louvres. With UGR of less than 19, these downlights are available in narrow, medium, and wide optics to suit various lighting needs. Whether creating welcoming atmospheres for guests or adding touches of elegance to residential spaces, OUT downlights deliver both high performances and aesthetic appeals for wide ranges of environments.



OUT 1 - 6W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	498lm	2700K	C001.06W015□927
		538lm	3000K	C001.06W015□930
		598lm	4000K	C001.06W015□940
	24°	496lm	2700K	C001.06W024□927
		536lm	3000K	C001.06W024□930
		595lm	4000K	C001.06W024□940
	35°	496lm	2700K	C001.06W035□927
		536lm	3000K	C001.06W035□930
		595lm	4000K	C001.06W035□940
	55°	494lm	2700K	C001.06W055□927
		534lm	3000K	C001.06W055□930
		593lm	4000K	C001.06W055□940

OUT 1 - 9W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	697lm	2700K	C002.09W015□927
		753lm	3000K	C002.09W015□930
		837lm	4000K	C002.09W015□940
	24°	694lm	2700K	C002.09W024□927
		750lm	3000K	C002.09W024□930
		833lm	4000K	C002.09W024□940
	35°	694lm	2700K	C002.09W035□927
		750lm	3000K	C002.09W035□930
		833lm	4000K	C002.09W035□940
	55°	692lm	2700K	C002.09W055□927
		747lm	3000K	C002.09W055□930
		830lm	4000K	C002.09W055□940