PAR-RS 1



Features

Displaying our PAR-RS 1, featuring a lumen output of 1359lm to 1637lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 12° to 36°, making it ideal for retail spaces and galleries. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

PAR-RS premium ceiling-mounted spotlights are designed to express elegance and a minimalist aesthetic, making them ideal choices for high-end spaces. Their modern and essential designs seamlessly integrate into any luxury environments, while their highly adjustable features ensure precise and customizable lighting. Perfect for showcasing artwork in galleries and exhibitions, enhancing the ambiance in libraries, or illuminating contemporary living spaces, PAR-RS offer both style and functionality, providing the ideal lighting solutions for premium interiors.





























www.elinca.it Downlights

PAR-RS 1 - 15W	Optics	Output	ССТ	Part number
	12°	1365lm	2700K	F028.15W012□927
		1474lm	3000K	F028.15W012□930
		1637lm	4000K	F028.15W012□940
	24°	1359lm	2700K	F028.15W024□927
		1468lm	3000K	F028.15W024□930
		1631lm	4000K	F028.15W024□940
	36°	1359lm	2700K	F028.15W036□927
		1468lm	3000K	F028.15W036□930
- · · · · · · · · · · · · · · · · · · ·		1631lm	4000K	F028.15W036□940
☐ refers to finishing:				
B: Black, W: White.				
Standard configuration:				
W, white body, black ring.				
Other CCT upon request.				

