PAR-RS 3



Features

Displaying our PAR-RS 3, featuring a lumen output of 2199lm to 2650lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 12° to 36°, making it ideal for retail spaces and galleries. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

PAR-RS premium ceiling-mounted spotlights are designed to express elegance and a minimalist aesthetic, making them ideal choices for high-end spaces. Their modern and essential designs seamlessly integrate into any luxury environments, while their highly adjustable features ensure precise and customizable lighting. Perfect for showcasing artwork in galleries and exhibitions, enhancing the ambiance in libraries, or illuminating contemporary living spaces, PAR-RS offer both style and functionality, providing the ideal lighting solutions for premium interiors.





























www.elinca.it Downlights

PAR-RS 3 - 28W	Optics	Output	ССТ	Part number
	12°	2208lm 2385lm 2650lm	2700K 3000K 4000K	F030.28W012□927 F030.28W012□930 F030.28W012□940
	24°	2199lm 2375lm 2639lm	2700K 3000K 4000K	F030.28W024□927 F030.28W024□930 F030.28W024□940
☐ refers to finishing: B: Black, W: White. Standard configuration: W, white body, black ring. Other CCT upon request.	36°	2199lm 2375lm 2639lm	2700K 3000K 4000K	F030.28W024□927 F030.28W024□930 F030.28W024□940

