


# PIN 3



**Light output:** up to 1218lm   **Cut out:** ø45mm   **Standard finishing:** ● ○

## Features

Displaying our PIN 3, featuring a lumen output of 1011lm to 1218lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 18° to 50°, making it ideal for hotels. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

## Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

## Applications

PIN downlights are highly efficient compact pin-hole downlights that deliver outstanding performance, making them the best in their class for delivered lumens relative to their diameters. Their minimal designs reduce visual impact while enhancing the aesthetic appeal of any space. PIN downlights also excel in glare control, ensuring a comfortable and visually pleasing environment. Whether for residential or commercial use, these fixtures provide superior lighting solutions that highlight architectural features and artworks without distraction. Their sleek profiles and advanced technologies make them perfect choices for those seeking both functionality and elegance in their lighting design.



**PIN 3 - 12W**

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	18°	1015lm	2700K	A105.12W018□927
		1096lm	3000K	A105.12W018□930
		1218lm	4000K	A105.12W018□940
	24°	1015lm	2700K	A105.12W024□927
		1096lm	3000K	A105.12W024□930
		1218lm	4000K	A105.12W024□940
	36°	1012lm	2700K	A105.12W036□927
		1093lm	3000K	A105.12W036□930
		1214lm	4000K	A105.12W036□940
	50°	1011lm	2700K	A105.12W050□927
		1092lm	3000K	A105.12W050□930
		1213lm	4000K	A105.12W050□940