POP-UP 1



Features

Showcasing our POP-UP 1, featuring a lumen output of 554lm to 669lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 12° to 36°, making it ideal for retail and art gallery spaces. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

POP-UP adjustable recessed projectors are perfect solutions for lighting up retail spaces, art galleries, and car showrooms. The high CRI ensures colours are seen in their natural, vivid forms. Their extreme adjustability and the ability to retract the bodies completely offer great flexibility and adaptability, making them ideal for quick changes in settings. This makes POP-UP versatile and efficient solutions for environments that require frequent transformations.



























www.elinca.it Downlights

POP-UP 1 - 7W	Optics	Output	ССТ	Part number
	15°	558lm 602lm	2700K 3000K	A107.07W015□927 A107.07W015□930
		669lm	4000K	A107.07W015□940
	24°	556lm	2700K	A107.07W024□927
		600lm	3000K	A107.07W024□930
		667lm	4000K	A107.07W024□940
	38°	554lm	2700K	A107.07W038□927
		598lm	3000K	A107.07W038□930
		665lm	4000K	A107.07W038□940
☐ refers to finishing: B: Black, W: White. Other CCT upon request.				

